

014-0034 

SGI 6s, Sight glass, Solder, ODF, Solder, ODF

Inlet connection type: Solder, ODF, Outlet connection type: Solder, ODF



PRODUCT DETAILS

Gross weight	0.105 Kilogram
Net weight	0.089 Kilogram
Volume	0.143 Liter
EAN	5702422039532
Body material	Brass
China RoHS compliance	Yes exceed limitations
Connection material	Copper
Contain batteries	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Green: max moist con@25 °C	R22: 150 ppm
Green: max moist con@43 °C	R22: 250 ppm
Inlet connection type	Solder, ODF
Inlet size [in]	1/4 in
Max. Working Pressure [bar]	35 bar
Max. Working Pressure [psig]	500 psig
Moisture indicator	I indicator
Outlet connection type	Solder, ODF
Outlet size [in]	1/4 in
Packing format	Multi pack
Product accessories	No
Product group	Sight glasses
Product Name Description	Sight glass
Quantity per packing format	25 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1) Cobalt dichloride (CAS no. 7646-79-9)
Refrigerants	R22
SCIP dossier no.	323c7b85-ff73-43cd-8fce-a44eabbf5297
Serviceable	No
Temperature range [°C] [max]	80 °C
Temperature range [°C] [min]	-50 °C
Temperature range [°F] [max]	175 °F
Temperature range [°F] [min]	-58 °F
Type	SGI 6s
UK RoHS compliance	Out of scope
Yellow: min moist con@25 °C	R22: 300 ppm

**PRODUCT DETAILS**

Yellow: min moist con@43 °CR22: 500 ppm

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)