

**017D001366** **Differential pressure switch, RT262A**

Diff.press.setting range [bar]: 0.1 - 1.5, Reset function: Auto, Pressure connection type: M, Pressure connection size: 12 x 1.5, Enclosure rating IP: IP66, Max. Working Pressure [bar]: 11

PRODUCT DETAILS

Gross weight	1.24 Kilogram
Net weight	0.962 Kilogram
Volume	4.715 Liter
EAN	5702428042895
Ambient temperature range [°C] [max]	70 °C
Ambient temperature range [°C] [min]	-40 °C
Ambient temperature range [°F] [max]	158 °F
Ambient temperature range [°F] [min]	-40 °F
Approval	CCC CE CMIM EAC KR LLC CDC EURO-TYSK LVD PZH RINA RMRS RoHS RoHS China TYSK
CE evaluated	Yes
China RoHS compliance	Yes
Contact differential [bar]	0.1 bar
Contact function	SPDT+SPST
Contact rating	AC15=3 A, 400 V AC1=10 A, 400 V AC3=4 A, 400 V DC13=12 W, 220 V LR=28 A, 400 V
Contain batteries	No
Diff.press.setting range [bar] [max]	1.5 bar
Diff.press.setting range [bar] [min]	0.1 bar
Diff.press.setting range [MPa] [max]	0.15 MPa
Diff.press.setting range [MPa] [min]	0.01 MPa
Diff.press.setting range [psi] [max]	22 psi

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



PRODUCT DETAILS

Diff.press.setting range [psi] [min]	1.5 psi
EEE category	5 small equipment (any external dimension < 50 cm)
Electrical conn. Male/Female	Female
Electrical connection	Screwed cable entry
Electrical connection size	2xPg 13.5
Electrical connection standard	DIN 40430
Electrical spec. standard	EN 60947-4/-5
EN 60947 electrical properties	Insulation: 400V Pollution degree: 3 Rated impulse voltage: 4 kV Short circuit prot, fuse: 10A
EN 60947 wiring properties	Flex, ferrules: 0.2-1.5 mm ² Flex, no ferrules: 0.2-2.5 mm ² Solid/stranded: 0.2-2.5 mm ²
Enclosure rating IP	IP66
EU RoHS compliance	Yes
EU RoHS exemption clause	No
In scope of WEEE	Yes
Max. test pressure [bar] Pe	13 bar
Max. test pressure [psig]	188 psig
Max. Working Pressure [bar]	11 bar
Max. Working Pressure [psig]	160 psig
Operat. range LP side [bar] Pe [max]	9 bar
Operat. range LP side [bar] Pe [min]	-1 bar
Operat. range LP side [psig]Pe [max]	131 psig
Operat. range LP side [psig]Pe [min]	-15 psig
Packing format	Multi pack
Pressure connection notes	Cutting ring 6mm tube
Pressure connection size	12 x 1.5
Pressure connection standard	ISO 8434-1
Pressure connection type	M
Pressure Male/Female	Male
Pressure range [bar] Pe [max]	9 bar
Pressure range [bar] Pe [min]	-1 bar
Product accessories	Generic accessories Switches accessories
Product description	Diff. Pressure Switch
Product group	Switches and thermostats
Product Name Description	Differential pressure switch
Quantity per packing format	9 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerants	R11 R12 R123 R124 R134a R22 R404A R407A R407C R407F

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Differential pressure switch, RT262A

PRODUCT DETAILS

	R407H
	R422B
	R422D
	R438A
	R507C
	R717
Relay release time [s]	0 s
Reset function	Auto
SCIP dossier no.	f62fe422-beda-433a- a602-740419c82c06
SCIP dossier product name	RT Presso_Diff.Presso
Serviceable	Contact systems
Type	RT262A
UK RoHS compliance	Yes
UL approved refrigerants	R11
	R12
	R123
	R124
	R134a
	R22
	R404A
	R407A
	R407C
	R407F
	R407H
	R422B
	R422D
	R438A
	R507C

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)